

[0037] CLAIM OR CLAIMS

[0038] What I claim as my invention is:

[0039] 1. A restraint for walking or other activity comprising:

(a) a primary strap of sufficient length to circle the restrainee's body and long enough to be held by a guardian;

(b) a first secondary strap attached left of the center of the primary strap;

(c) a second secondary strap attached right of the center of the primary strap;

(d) each secondary strap having a loop on the non-attached end; and

(e) each secondary strap being of sufficient length to pass around the restrainee's body, cross, and allow the primary strap to be threaded through each secondary strap loop at the restrainee's back.

[0040] 2) The invention as described in Claim 1 wherein:

(a) the primary strap is placed horizontally across the front of the restrainee at the level of the axillae;

(b) the left secondary strap is brought over the restrainee's left shoulder to the restrainee's back;

(c) the right secondary strap is brought over the restrainee's right shoulder to the restrainee's back;

(d) the left and right secondary straps are crossed;

- 1 (e) the left end of the primary strap is brought under the restrainee's left
2 axilla and threaded through the loop at the end of the right secondary
3 strap;
4 (f) the right end of the primary strap is brought under the restrainee's
5 right axilla and threaded through the loop at the end of the left
6 secondary strap; and
7 (g) the ends of the primary strap being held by the guardian so as to
8 restrain the restrainee.
9

10 **[0041]** 3) The invention as described in Claim 1 wherein:

- 11 (a) the primary strap is placed horizontally across the front of the
12 restrainee at the level of the axillae;
13 (b) the left secondary strap is brought over the restrainee's left shoulder
14 to the restrainee's back;
15 (c) the right secondary strap is brought over the restrainee's right
16 shoulder to the restrainee's back;
17 (d) the left end of the primary strap is brought under the restrainee's left
18 axilla and threaded through the loop at the end of the left secondary
19 strap and then through the loop at the end of the right secondary
20 strap;
21 (e) the right end of the primary strap is brought under the restrainee's
22 right axilla and threaded through the loop at the end of the right

1 secondary strap and then through the loop at the end of the left

2 secondary strap; and

3 (f) the ends of the primary strap being held by the guardian so as to
4 restrain the restrainee.

5
6 **[0042]** 4) The invention as described in Claim 1 wherein:

7 (a) the primary strap is placed horizontally across the front of the
8 restrainee at the level of the axillae;

9 (b) the left secondary strap is brought over the restrainee's left shoulder
10 to the restrainee's back;

11 (c) the right secondary strap is brought over the restrainee's right
12 shoulder to the restrainee's back;

13 (d) the left end of the primary strap is brought under the restrainee's left
14 axilla and threaded through the loop at the end of the left secondary
15 strap;

16 (e) the right end of the primary strap is brought under the restrainee's
17 right axilla and threaded through the loop at the end of the right
18 secondary strap; and

19 (f) the ends of the primary strap being held by the guardian so as to
20 restrain the restrainee.

1 **[0043]** 5) The invention as described in Claim 1 wherein:

2 (a) the primary strap is placed horizontally across the front of the
3 restraineed at the level of the shoulders;

4 (b) the left secondary strap is brought under the restraineed's left axilla to
5 the restraineed's back;

6 (c) the right secondary strap is brought under the restraineed's right axilla
7 to the restraineed's back;

8 (d) the left end of the primary strap is brought over the restraineed's left
9 shoulder and threaded through the loop at the end of the left
10 secondary strap;

11 (e) the right end of the primary strap is brought over the restraineed's right
12 shoulder and threaded through the loop at the end of the right
13 secondary strap; and

14 (f) the ends of the primary strap being held by the guardian so as to
15 restrain the restraineed.

16
17 **[0044]** 6) The invention as described in Claim 1 wherein:

18 (a) the primary strap is placed horizontally across the front of the
19 restraineed at the level of the shoulders;

20 (b) the left secondary strap is brought under the restraineed's left axilla to
21 the restraineed's back;

- 1 (c) the right secondary strap is brought under the restrainee's right axilla
2 to the restrainee's back;
3 (d) the left end of the primary strap is brought over the restrainee's left
4 shoulder and threaded through the loop at the end of the left
5 secondary strap and then through the loop at the end of the right
6 secondary strap;
7 (e) the right end of the primary strap is brought over the restrainee's right
8 shoulder and threaded through the loop at the end of the right
9 secondary strap and then through the loop at the end of the left
10 secondary strap; and
11 (f) the ends of the primary strap being held by the guardian so as to
12 restrain the restrainee.